


ALFRA ROTABEST® – RB 35/50 X PICCOLO



RB 35/50 X PICCOLO

Core drill dimensions	Ø 12.0 - 35.0 mm
Cutting depth	50.0 mm
Twist drill	Ø 1.0 - 13.0 mm
Counterboring	Ø 10.0 - 40.0 mm
Arbors	Quick-release chuck
Stroke	129 mm
Height adjustment	86 mm
Gearbox - on-load speed	450 rpm
Power consumption	1,100 W
Voltage	230 V 50/60 Hz 110 V 50/60 Hz
Tool force (10 mm) / magnetic adhesion strength	2,100 N/9,000 N
Magnetic base	70 x 185 mm
Weight	11.5 kg

Motor	
Smooth start	✓
Hybrid relay	✓
Overload protection	✓
Motor emergency stop	✓
Gearboxes	
Oil-box gearbox	✓
Slides	
Infinitely adjustable	✓
Self-adjusting guide	✓
Operation	
Soft-touch grips	✓
Membrane keyboard	✓
Holder for Allen key	✓
Cable length 5 m	✓
Magnet	
Sensor/LED	✓
Metal rings	✓
Performance and weight optimisation	✓
Made in Germany ✓	

Scope of delivery	
<ul style="list-style-type: none"> • Metal core drilling machine RB 35/50 X Piccolo • Carrying case • Seat belt • Coolant device • Operating Instructions • incl. 1 core drill free 	



Prod.-No.

ALFRA Rotabest® RB 35/50 X Piccolo 230 Volt

18701

ALFRA Rotabest® RB 35/50 X Piccolo 110 Volt

18701.110